

## 30V N-Channel Enhancement Mode MOSFET

### 1. Product Information

#### 1.1 Features

- ◇ Surface-mounted package
- ◇ Advanced TRENCH cell design



#### 1.2 Applications

- ◇ Motor appliances
- ◇ High power inverter system

#### 1.3 Quick reference

- ◇  $BV \cong 30\text{ V}$
- ◇  $P_{\text{tot}} \cong 35\text{ W}$
- ◇  $I_D \cong 72\text{ A}$
- ◇  $R_{\text{DS(ON)}} \cong 6.8\text{ m}\Omega @ V_{\text{GS}} = 10\text{ V}$
- ◇  $R_{\text{DS(ON)}} \cong 8.5\text{ m}\Omega @ V_{\text{GS}} = 4.5\text{ V}$

### 2. Pin Description



### 3. Marking Information

Product Name	Marking
LN068N030G	LN068N030G CYWWZZ XXXXXX

## 4. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
$V_{DS}$	Drain-Source Voltage	$T_A = 25\text{ }^\circ\text{C}$	30	-	V
$V_{GS}$	Gate-Source Voltage	$T_A = 25\text{ }^\circ\text{C}$	-	$\pm 20$	V
$I_D^*$	Drain Current	$T_A = 25\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	72	A
		$T_A = 100\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	45	A
$I_{DM}^{*,**}$	Pulsed Source Current	$T_A = 25\text{ }^\circ\text{C}, V_{GS} = 10\text{ V}$	-	150	A
$P_{tot}$	Total Power Dissipation	$T_A = 25\text{ }^\circ\text{C}$	-	35	W
$T_{stg}$	Storage Temperature		- 55	150	$^\circ\text{C}$
$T_J$	Junction Temperature		- 55	150	$^\circ\text{C}$
$I_S$	Diode Forward Current	$T_A = 25\text{ }^\circ\text{C}$	-	80	A
$R_{\theta JA}^*$	Thermal Resistance- Junction to Ambient		-	42	$^\circ\text{C}/\text{W}$

Notes :

\* Surface Mounted on 1 in<sup>2</sup> pad area,  $t \leq 10\text{ sec}$

\*\* Pulse width  $\leq 300\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$

## 5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
<b>LN068N030G</b>	<b>PDFN5*6</b>			<b>5000</b>	

Note: COMTECH defines " Green " as lead-free ( RoHS compliant ) and halogen free ( Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C )

## 6. Electrical Characteristics (TA=25 ° Unless Otherwise Noted )





Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_{DS} = 250\ \mu\text{A}$	30	-	-	V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_{DS} = 250\ \mu\text{A}$	1.0	-	2.0	V
$I_{DSS}$	Drain Leakage Current	$V_{DS} = 24\text{ V}, V_{GS} = 0\text{ V}$	-	-	1	$\mu\text{A}$
		$T_J = 85^\circ\text{C}$	-	-	30	$\mu\text{A}$
$I_{GSS}$	Gate Leakage Current	$V_{GS} = \pm 20\text{ V}, V_{DS} = 0\text{ V}$	-	-	$\pm 100$	nA
$R_{DS(ON)}^a$	On-State Resistance	$V_{GS} = 10\text{ V}, I_{DS} = 10\text{ A}$	-	5.7	6.8	m $\Omega$
		$V_{GS} = 4.5\text{ V}, I_{DS} = 5\text{ A}$	-	7.5	8.5	
<b>Diode Characteristics</b>						
$V_{SD}^a$	Diode Forward Voltage	$I_{SD} = 10\text{ A}, V_{GS} = 0\text{ V}$	-	-	1.3	V
$t_{rr}$	Reverse Recovery Time	$I_{DS} = 10\text{ A}, V_{GS} = 0\text{ V}$	-	34	-	nS
$Q_{rr}$	Reverse Recovery Charge	$dI_{SD}/dt = 100\text{ A}/\mu\text{s}$	-	7.1	-	nC
<b>Dynamic Characteristics<sup>b</sup></b>						
$C_{ISS}$	Input Capacitance	$V_{GS} = 0\text{ V}, V_{DS} = 15\text{ V}$ Frequency = 1 MHz	-	1145	-	pF
$C_{OSS}$	Output Capacitance		-	106	-	
$C_{rSS}$	Reverse Transfer Capacitance		-	87	-	
$t_d(on)$	Turn-on Delay Time	$V_{DS} = 15\text{ V}, V_{GEN} = 10\text{ V},$ $R_G = 4.5\ \Omega, R_L = 1.5\ \Omega,$ $I_{DS} = 10\text{ A}$	-	7	-	nS
$t_r$	Turn-on Rise Time		-	30	-	
$t_d(off)$	Turn-off Delay Time		-	19	-	
$t_f$	Turn-off Fall Time		-	18	-	
<b>Gate Charge Characteristics<sup>b</sup></b>						
$Q_g$	Total Gate Charge	$V_{GS} = 15\text{ V}, V_{DS} = 10\text{ V},$ $I_{DS} = 10\text{ A}$	-	22	-	nC
$Q_{gs}$	Gate-Source Charge		-	5	-	
$Q_{gd}$	Gate-Drain Charge		-	3.3	-	

Notes :





a : Pulse test ; pulse width  $\leq 300\ \mu\text{s}$ , duty cycle  $\leq 2\%$ 

b : Guaranteed by design, not subject to production testing





## 7. Typical Characteristics



## 7. Typical Characteristics (cont.)



## 7. Typical Characteristics (cont.)



## 8. Package Dimensions

### PDFN5\*6-8L Package

