100V N-Channel Enhancement Mode MOSFET

1.Product Information

1.1 Features

- ◇ Advanced SGT cell design
- ◇ Low Gate Charge
- ◇ Low On-Resistance
- ◇ RoHS and Halogen-Free Compliant
- ◇ 100% ΔVDS & UIS & Rg Tested

1.2 Applications

- ◇ DC-DC Converter
- ◇ Drones
- ◇ Motor drivers
- ◇ Light electric vehicles

1.3 Quick reference


- ◇ BV ≧ 100 V
- ◇ P_{tot} ≦ 204 W
- ◇ I_D ≦ 111 A
- ◇ $R_{DS(ON)}$ ≦ 12.0 mΩ @ V_{GS} = 10V
- ◇ $R_{DS(ON)}$ ≦ 23.0 mΩ @ V_{GS} = 6.0V

Green Product

RoHS

2.Pin Description


Symbol



Simplified Outline

Top View

PDFN5*6



3.Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit	Note
V_{DS}	Drain-Source Voltage	T_C = 25 ℃	-	100	V	-
V_{GS}	Gate-Source Voltage	T_C = 25 ℃	-	±20	V	-
I_D*	Drain Current (DC)	T_C = 25 ℃, V_{GS} = 10 V	-	111	A	Fig.2
		T_C = 100 ℃, V_{GS} = 10 V	-	70	A	
I_{DM}**,***	Drain Current (Pulsed)	T_C = 25 ℃, V_{GS} = 10 V	-	183	A	-
P_{tot}	Drain power dissipation	T_C = 25 ℃	-	204	W	Fig.1
		T_C = 100 ℃	-	81	W	
	Linear reduction	T_A > 25 ℃	-	1.63	W/℃	
T_{stg}	Storage Temperature		-55	150	℃	-
T_J	Junction Temperature		-	150	℃	-
I_S	Continuous-Source Current	T_C = 25 ℃	-	111	A	-
E_{AS}*	Single Pulsed Avalanche Energy	V_{DD}=100V,L=0.3mH	-	205	mJ	Fig.19

4.Thermal Characteristics

$R_{\theta JA}$*	Thermal Resistance- Junction to Ambient	-	26	℃/W	Fig.16
$R_{\theta JC}$*	Thermal Resistance- Junction to Case	-	0.61		

Notes：

* Surface Mounted on 1 in² pad area, t ≤ 10 sec

** Pulse width ≤ 300 μs, duty cycle ≤ 2 %

*** limited by bonding wire

5.Marking Information

Product Name	Package	Reel size	Tape width	Quantity	Note
LN100N100G	PDFN5*6	330mm	12mm	5000	

Note: COMTECH defines " Green " as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight;Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)

6. Electrical Characteristics (T_A=25 ° Unless Otherwise Noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit	Note
Static Characteristics							
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0 V, I_{DS} = 250 μA	100	-	-	V	
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_{DS} = 250 μA	2	-	4	V	
I_{DSS}	Drain Leakage Current	V_{DS} =100V, V_{GS} = 0 V	-	-	1	μA	
I_{GSS}	Gate Leakage Current	V_{GS} = ± 20 V, V_{DS} = 0 V	-	-	±100	nA	
$R_{DS(ON)}$ [a]	On-State Resistance	V_{GS} =10V , I_{DS} =5A	-	10.0	12.0	mΩ	Fig.8
		V_{GS} =6.0V, I_{DS} =5A	-	16.0	23.0		
Diode Characteristics							
V_{SD} [a]	Diode Forward Voltage	I_{SD} = 5A , V_{GS} = 0 V	-	-	1.3	V	Fig.7
t_{rr}	Reverse Recovery Time	I_{DS} = 5A , V_{GS} = 0 V	-	44	-	nS	Fig.20
Q_{rr}	Reverse Recovery Charge	$dI_{SD/dt}$ = 100 A/μs	-	31	-	nC	
Dynamic Characteristics [b]							
C_{iss}	Input Capacitance	V_{GS} = 0 V, V_{DS} =50V Frequency = 1 MHz	-	2169	-	pF	Fig.10
C_{oss}	Output Capacitance		-	553	-		
C_{rss}	Reverse Transfer Capacitance		-	15	-		
R_G	Gate Resistance	F= 1 MHz	-	1.6	-	Ω	
t_d(on)	Turn-on Delay Time	V_{DS} = 50V, V_{GS} = 10 V, $RG_{(ext)}$=2.7Ω, R_L=100uH I_{DS} = 5A	-	24	-	nS	Fig.18
t_r	Turn-on Rise Time		-	42	-		
t_d(off)	Turn-off Delay Time		-	34	-		
t_f	Turn-off Fall Time		-	74	-		
dv/dt(on)	Turn-on Peak Diode Recovery		-	0.947	-	KV/us	
dv/dt(off)	Turn-off Peak Diode Recovery		-	0.542	-		
di/dt(on)	Turn-on Peak Diode Recovery		-	363	-	A/us	
di/dt(off)	Turn-off Peak Diode Recovery		-	302	-		
Gate Charge Characteristics [b]							
Q_g	Total Gate Charge	V_{DS} =50V , V_{GS} = 10 V, I_{DS} = 5A	-	28	-	nC	Fig.9
Q_{gs}	Gate-Source Charge		-	7	-		
Qgd	Gate-Drain Charge		-	5	-		
Vplateau	Gate plateau voltage		-	4.4	-	V	

Notes :
a : Pulse test ; pulse width ≤ 300 μs, duty cycle ≤ 2%
b : Guaranteed by design, not subject to production testing

7. Typical Characteristics

Fig.1 Power Capability




Fig.2 Current Capability




Fig.3 Output Characteristics@Tj -55°C





Fig.4 Output Characteristics@Tj 25°C



专业、 先进、 高效的国产半导体功率集成电路制造商
技术支持： 400-888-7385
镭诺电子 （宁波） 有限公司
www.leinuosemi.com

7. Typical Characteristics

Fig.5 Output Characteristics@Tj 150°C




Fig.6 Transfer Characteristics vs Temp




Fig.7 Body Diode Characteristics





Fig.8 Drain-Source On Resistance



专业、 先进、 高效的国产半导体功率集成电路制造商
技术支持： 400-888-7385
镭诺电子 （宁波） 有限公司
www.leinuosemi.com

7. Typical Characteristics

Fig.9 Gate Charge




Fig.10 Capacitance




Fig.11 Normalized Threshold Voltage






Fig.12 Normalized Breakdown Voltage



专业、 先进、 高效的国产半导体功率集成电路制造商
技术支持： 400-888-7385
镭诺电子 （宁波） 有限公司
www.leinuosemi.com


7. Typical Characteristics

Fig.13 Normalized On Resistance




T_j - Junction Temperature (°C)

Fig.14 Switching Energy vs ID




I_{DS}- Drain-Source Current. (A)

Fig.15 Safe Operating Area



V_{DS} - Drain-Source Voltage (V)

Fig.16 Transient Thermal Impedance



Square Wave Pulse Duration (sec)

专业、 先进、 高效的国产半导体功率集成电路制造商
技术支持： 400-888-7385
镭诺电子 （宁波） 有限公司
www.leinuosemi.com

7. Typical Characteristics

Fig.17 Gate Charge Test Circuit & Waveform




Fig.18 Resistive Switching Test Circuit & Waveforms




Fig.19 Unclamped Inductive Switching (UIS) Test Circuit & Waveforms






Fig.20 Diode Recovery Test Circuit & Waveforms



专业、 先进、 高效的国产半导体功率集成电路制造商
技术支持： 400-888-7385
镭诺电子 （宁波） 有限公司
www.leinuosemi.com

8. Package Dimensions

PDFN5*6 Package



Symbol	Dimensions In Millimeters		
	MIN.	NOM.	MAX.
A	0.900	1.000	1.100
D	4.950	5.050	5.150
D1	3.850	4.050	4.250
E	5.750	5.850	5.950
E1	5.950	6.150	6.350
E2	3.300	3.500	3.700
E3	0.900	1.100	1.300
b	0.250	0.300	0.350
e	1.220	1.270	1.320
L	0.585	0.685	0.785
L1	0.525	0.625	0.725
Ø	1.000	1.200	1.400
L2	0~0.100		
L3	0~0.100		

9. Record of Document amendment

产品名称：LN100N100G
版权说明：镭诺电子（宁波）有限公司
联系电话：4008887385

文档类型：产品手册
公司主页：www.leinuosemi.com

版本：01
修改记录：
1.初版发行